


- 1 DEMOLISH EXISTING LAVATORY. CUT AND CAP WASTE AND WATER CONNECTIONS BACK TO POINT OF USE AS REQUIRED.
- 2 DEMOLISH EXISTING WATER CLOSET. CUT AND CAP WASTE AND WATER CONNECTIONS BACK TO POINT OF USE AS REQUIRED.
- 3 DEMOLISH EXISTING FIXTURE. CUT AND CAP WASTE AND WATER CONNECTIONS BACK TO POINT OF USE AS REQUIRED.
- 4 DEMOLISH EXISTING WATER HEATER. CUT AND CAP WASTE AND WATER CONNECTIONS BACK TO POINT OF USE AS REQUIRED.
- 5 DEMOLISH EXISTING FLOOR SINK. CUT AND CAP WASTE AND WATER CONNECTIONS BACK TO POINT OF USE AS REQUIRED.
- 6 NEW WATER HEATER SUSPENDED ABOVE ACCESSIBLE CEILING. COORDINATE WITH MEP IN THE AREA. REFER TO DETAILS.
- 7 CONNECT NEW 1" COLD WATER TO EXISTING WATER ABOVE CEILING. VERIFY SIZE AND LOCATION PRIOR TO START OF WORK.
- 8 PROVIDE NEW 2" VENT TO THROUGH ROOF.
- 9 CONNECT NEW 4" WASTE TO EXISTING WASTE BELOW SLAB. BYPASS EXISTING GREASE TRAP. VERIFY SIZE AND LOCATION PRIOR TO START OF WORK.
- 10 EXISTING GREASE TRAP TO REMAIN. CAP EXISTING INLET LINE.
- 11 REFRIGERATOR BY OTHERS - PLUMBING CONTRACTOR TO PROVIDE COLD WATER CONNECTION CONSISTING OF 1/2" X 3/8" ANGLE PATTERN COMPRESSION STOP 12" A.F.F. (RVB-1)

[illegible]

P-2.00

