

WC-1

CADET® PRO™ RIGHT HEIGHT® ELONGATED TOILET
VITREOUS CHINA

215AA.104

- Features the **Cadet® Flushing System**
- Vitreous china
- High Efficiency Toilet (HET), ultra-low consumption (4.8 Lp/1.28 gpf), utilizes 20% less water
- Meets EPA WaterSense® criteria
- Trade exclusive tank
- PowerWash™ rim scrubs bowl with each flush
- Robust metal trip lever & metal shank fill valve
- Includes EZ-Install Tools w/color match bowl caps
- EverClean® surface included
- 3" flush valve
- Fully-glazed 2-1/8" trapway
- 16-1/2" rim height for accessible applications
- 12" (305mm) rough-in
- Generous 9" x 8" water surface area
- Chrome finish trip lever is supplied
- 1,000g MaP Score** at 1.28 gpf
- 5 year warranty

215AA.105 Same as above except with trip lever on right side

3517A.101 Right Height® Elongated Bowl

4188A.104 Tank

Nominal Dimensions:
767 x 441 x 771mm (30-1/8" x 17-3/8" x 30-3/8")

Fixture only, seat and supply sold separately

Alternative Tank Configurations Available:

- **4188A.154** Tank complete with Aquaguard Liner
- **4188A.155** Tank complete with Aquaguard Liner and trip lever located on right side
- **4188A.164** Tank complete with tank cover locking device
- **4188A.174** Tank complete with Aquaguard Liner and tank cover locking device
- **4188A.105** Tank complete with trip lever located on right side
- **4188A.165** Tank complete with tank cover locking device and trip lever located on right side

Compliance Certifications - Meets or Exceeds the Following Specifications:

- ASME A112.19.2-2008/CSA B45.1-08 for Vitreous China Fixtures
- US EPA WaterSense® Specification for HETs

**** Maximum Performance (MaP) testing performed by IAPMO R&T Lab. MaP Report conducted by Veritec Consulting, Inc. and Koeller and Company.**

To Be Specified:

- Color: □ White □ Bone □ Linen □ Black
- Seat: #5321.110 EverClean® Elongated Seat with Slow Close Snap-Off Hinges
- Supply with stop:

CADET® PRO™ RIGHT HEIGHT® ELONGATED TOILET

FINISHED WALL

CL OF SEAT POST HOLES

CL OF OUTLET

FINISHED FLOOR

NOTES:
THIS TOILET IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12") FROM FINISHED WALL TO CL OF OUTLET. SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY. DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES.

WaterSense®

Water Efficient Product

Cadet® PRO

K168 Rev. 6/13

EDF-1

Model HTHB-HAC8BLSS-WF
HydroBoost® Bottle Filling Station & Bi-Level ADA Cooler Filtered Refrigerated Stainless

PRODUCT SPECIFICATIONS

Special Features: Antimicrobial, Filtered, Green Counter™, Laminar Flow, Mechanically Activated, Real Drain, Sanitary Sensor Activated, Visual Filter Monitor

Finish: Stainless Steel (S)

Power: 115V/60Hz

Bubbler Style: Double Bubbler™

Activation by: Electronic Bottle Filler Sensor with Mechanical Front and Side Bubbler Pushbar

Mounting Type: Wall Mount (On Wall)

Chilling Capacity: 8.0 GPH

Full Load Amps: 6

Rated Watts: 370

Dimensions (L x W x H): 36-1/4" x 18-5/8" x 46-1/4"

Approx. Shipping Weight: 111 lbs.

Installation Location: Indoor

No. of Stations Served: 2

Based on 80° F inlet water & 80° F ambient air temp for 50° F chilled drinking water.

Included with Product: Water Cooler (8740082883-HTHB), Filter, Bottle Filler (HTHB-HAC)

Ships in multiple boxes.
A Century of Tradition and Quality. For more than 100 years, Ekay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.

PRODUCT COMPLIANCE

ADA & ICC A117.1
ASME A112.19.3/CSA B45.4
CAN/CSA C22.2 No. 120
GreenSpec®

NSF/ANSI 42, 53, 61 (Qs1), 372 (lead free), & 401 UL 399

UL US

GreenSpec LISTED

Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF) - 1000001743

5 Year Limited Warranty on the refrigeration system of the unit. Electrical components and water system are warranted for 12 months from date of installation. **Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty.**

Warranty (PDF)

PART: _____ QTY: _____

PROJECT: _____

CONTACT: _____

DATE: _____

NOTES:

APPROVAL: _____

Laminar flow provides clean fill with minimal splash.

In keeping with our policy of continuing product improvement, Halsey Taylor reserves the right to change product specifications without notice. Please visit HalseyTaylor.com for the most current version of Halsey Taylor product specification sheets. This specification describes a Halsey Taylor product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

Halsey Taylor REV 04022026
HTHB-HAC8BLSS-WF

1-800-260-6640 | SVTechservice@Ekay.com
Patent zurn-ekay.com/patents

© 2026 Page 1
HTHB-HAC8BLSS-WF_spec.pdf

The information, ideas, designs, details, layouts, techniques, features, arrangements, plans, sequences, dimensions, allowances, tolerances, conceptions, specifications, intentions, technology or embodiments, as illustrated, arranged, displayed, noted, recorded, indicated, represented, disclosed, evidenced, detailed or otherwise reduced to tangible form hereon, either expressly, inherently or by implication, are the confidential and proprietary information of SLI Design, Inc., and shall not be used for any purpose other than the specific project or undertaking identified on the drawing title block or legend for which they are and have been prepared by SLI Design, Inc. Any other reproduction, disclosure or use of any portion of the confidential and proprietary information of SLI Design, Inc., shall be a breach of the obligation of confidence created by the acceptance of this drawing from SLI Design, Inc. for a specific project or contract. Any copying, duplicating, reproducing, utilization, alteration, modification, revision or change to this drawing, is expressly prohibited unless done with the prior written consent or approval of SLI Design, Inc., and shall not be undertaken without receipt of such prior written approval. This drawing is loaned by SLI Design, Inc., for the limited purpose of complying with a specific contract. The drawing remains the property of SLI Design, Inc., and shall be returned upon request or completion of the contract, unless specifically authorized by contract, under which it was loaned.

10/07/2026

DRAWING TITLE
PLUMBING SPEC SHEETS
SHEET NO.
P-2.20